Material Safety Data Sheet



MIKROKLENE

Section 1. Chemical product and company identification

Trade name : MIKROKLENE
Product use : Sanitiser.
Supplier : Ecolab Co.

5105 Tomken Road

Mississauga ON L4W 2X5

1-800-352-5326

Code : 903363

Date of issue 06-August-2008

EMERGENCY HEALTH INFORMATION: 1-800-328-0026
Outside United States and Canada CALL 1-651-222-5352 (in USA)

Section 2. Composition, information on ingredients

<u>Name</u>	CAS number % by weight
oxirane, methyl-, polymer with oxirane, monobutyl ether	9038-95-3 7 - 13
phosphoric acid	7664-38-2 5- 10
iodine	7553-56-2 1 - 5
2-butoxyethanol	111-76-2 1 - 5

Section 3. Hazards identification

Physical state : Liquid. [Liquid.]
Emergency : DANGER!
overview

CAUSES DIGESTIVE TRACT, EYE AND SKIN BURNS.

CAUSES RESPIRATORY TRACT IRRITATION.
MAY CAUSE ALLERGIC SKIN REACTION.

Do not ingest. Do not get in eyes, on skin or on clothing. Avoid breathing vapours, spray or mists. Use only with adequate ventilation. Keep container closed. Wash thoroughly after

handling.

Routes of entry : Skin contact, Eye contact, Inhalation, Ingestion

Potential acute health effects

Eyes: Corrosive to eyes.

Skin: Corrosive to the skin. May cause sensitisation by skin contact.

Inhalation : Severely irritating to the respiratory system.Ingestion : Causes burns to mouth, throat and stomach.

See toxicological information (section 11)

Section 4. First-aid measures

Eye contact: In case of contact, immediately flush eyes with cool running water. Remove contact lenses and

continue flushing with plenty of water for at least 15 minutes. Get medical attention

immediately.

Skin contact: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while

removing contaminated clothing and shoes. Get medical attention immediately. Wash clothing

before reuse. Clean shoes thoroughly before reuse.

Inhalation: If inhaled, remove to fresh air. If exposed person is not breathing, give artificial respiration or

oxygen applied by trained personnel. Get medical attention immediately.

Ingestion: If material has been swallowed and the exposed person is conscious, give small quantities of

water to drink. Do not induce vomiting. Never give anything by mouth to an unconscious

person. Get medical attention immediately.

MIKROKLENE Page: 2/5

Section 5. Fire-fighting measures

Auto-ignition temperature

93.3333 °C (Closed cup)

: Not available.

Flammable limits

Flash point

: Not available.

Hazardous thermal decomposition products : Decomposition products may include the following materials:

carbon dioxide carbon monoxide phosphorus oxides halogenated compounds

Fire-fighting media and

instructions

: Use an extinguishing agent suitable for the surrounding fire.

Dyke area of fire to prevent runoff.

In a fire or if heated, a pressure increase will occur and the container may

burst.

fire-fighters

Special protective equipment for: Fire-fighters should wear appropriate protective equipment and self-contained

breathing apparatus (SCBA) with a full face-piece operated in positive pressure

mode.

Risk of explosion of the product in the presence of mechanical impact: Not available. Risk of explosion of the product in the presence of static discharge: Not available.

Section 6. Accidental release measures

Personal precautions : Immediately contact emergency personnel. Stop leak if without risk. Use suitable protective equipment. Keep unnecessary personnel away. Do not touch or walk through spilt material.

Environmental precautions

: Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

Methods for cleaning up

: If emergency personnel are unavailable, contain spilt material. For small spills, add absorbent (soil may be used in the absence of other suitable materials), scoop up material and place in a sealable, liquid-proof container for disposal. For large spills, dyke spilt material or otherwise contain it to ensure runoff does not reach a waterway. Place spilt material in an appropriate container for disposal.

Section 7. Handling and storage

Handling

: Do not ingest. Do not get in eyes, on skin, or on clothing. Do not breathe vapour or spray. Keep container closed. Use only with adequate ventilation. Wash thoroughly after handling. Do not mix with bleach or other chlorinated products - will cause chlorine gas.

Storage

: Keep out of reach of children. Keep container in a cool, well-ventilated area. Keep container tiahtly closed.

Do not store above the following temperature: 40°C

Section 8. Exposure controls/personal protection

Engineering measures

: Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapour or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. Provide suitable facilities for quick drenching or flushing of the eyes and body in case of contact or splash hazard.

Personal protection:

Eyes

: Use chemical splash goggles. For continued or severe exposure wear a face shield over the goggles.

Hands

: Use chemical-resistant, impervious gloves.

Skin

: Use synthetic apron, other protective equipment as necessary to prevent skin contact.

Respiratory

: Wear appropriate respirator when ventilation is inadequate and occupational exposure limits

are exceeded.

<u>Name</u>

Exposure limits

MIKROKLENE Page: 3/5

phosphoric acid CA Alberta Provincial (Canada, 10/2006).

15 min OEL: 3 mg/m³ 15 minute(s).

CA British Columbia Provincial (Canada, 7/2007).

STEL: 3 mg/m³ 15 minute(s). TWA: 1 mg/m³ 8 hour(s).

CA Ontario Provincial (Canada, 3/2007).

STEV: 3 mg/m³ 15 minute(s). TWAEV: 1 mg/m³ 8 hour(s).

CA Quebec Provincial (Canada, 12/2006).

STEV: 3 mg/m³ 15 minute(s). TWAEV: 1 mg/m³ 8 hour(s).

ACGIH TLV (United States, 1/2007).

STEL: 3 mg/m³ 15 minute(s). TWA: 1 mg/m³ 8 hour(s).

iodine CA Alberta Provincial (Canada, 10/2006).

15 min OEL: 1 mg/m³ 15 minute(s). 15 min OEL: 0.1 ppm 15 minute(s).

CA British Columbia Provincial (Canada, 7/2007).

STEL: 0.1 ppm 15 minute(s).

CA Ontario Provincial (Canada, 3/2007).

CEV: 1 mg/m³ CEV: 0.1 ppm

CA Quebec Provincial (Canada, 12/2006).

STEV: 1 mg/m³ 15 minute(s). STEV: 0.1 ppm 15 minute(s).

ACGIH TLV (United States, 1/2007).

C: 1 mg/m³ C: 0.1 ppm

2-butoxyethanol CA Alberta Provincial (Canada, 10/2006). Absorbed through skin.

8 hrs OEL: 97 mg/m³ 8 hour(s). 8 hrs OEL: 20 ppm 8 hour(s).

CA British Columbia Provincial (Canada, 7/2007).

TWA: 20 ppm 8 hour(s).

CA Ontario Provincial (Canada, 3/2007). Absorbed through skin.

TWAEV: 20 ppm 8 hour(s).

CA Quebec Provincial (Canada, 12/2006).

TWAEV: 97 mg/m³ 8 hour(s). TWAEV: 20 ppm 8 hour(s).

ACGIH TLV (United States, 1/2007).

TWA: 20 ppm 8 hour(s).

Section 9. Physical and chemical properties

Physical state: Liquid. [Liquid.]Colour: Brown. [Dark]Odour: Faint odour.

pH : 1.75 [Conc. (% w/w): 100%]

Boiling/condensation point: Not available.Melting/freezing point: Not available.Relative density: 1.077Vapour pressure: Not available.

Vapour pressure: Not available.Vapour density: Not available.Odour threshold: Not available.Evaporation rate: Not available.LogKow: Not available.

MIKROKLENE Page: 4/5

Section 10. Stability and reactivity

Stability

: The product is stable. Under normal conditions of storage and use, hazardous polymerisation will not occur.

Conditions of instability

Reactivity

Not available.

: Highly reactive or incompatible with the following materials: alkalis. Reactive or incompatible with the following materials: metals.

Slightly reactive or incompatible with the following materials: organic materials and

moisture.

Do not mix with bleach or other chlorinated products – will cause chlorine gas.

Hazardous decomposition

products

: Under normal conditions of storage and use, hazardous decomposition products

should not be produced.

Hazardous polymerisation

: Under normal conditions of storage and use, hazardous polymerisation will not

occur.

Section 11. Toxicological information

Potential acute health effects

Eyes : Corrosive to eyes.

Skin : Corrosive to the skin. May cause sensitisation by skin contact.

InhalationIngestionSeverely irritating to the respiratory system.Causes burns to mouth, throat and stomach.

Potential chronic health effects

Carcinogenic effects: No known significant effects or critical hazards.

Ingredient name ACGIH IARC NTP OSHA

Not applicable.

Mutagenic effects: No known significant effects or critical hazards.Teratogenic effects: No known significant effects or critical hazards.Reproductive effects: No known significant effects or critical hazards.Sensitization to Product: May cause sensitisation by skin contact.

Synergistic products : N

(toxicologically)

: Not available.

Toxicity data

Ingredient name	<u>Test</u>	Route Property of the Indian	<u>Result</u>	Species
oxirane, methyl-, polymer with oxirane, monobutyl ether	LC50	Inhalation	4670 mg/m³	Rat
iodine	LD50	Oral	14 g/kg	Rat
	LD50	Oral	10 g/kg	Rabbit
	LD50	Oral	22 g/kg	Mouse
	LD50	Oral	1000 mg/kg	Mouse
	LDLo	Oral	5 mg/kg	Rabbit
	LDLo	Oral	800 mg/kg	Dog
	LDLo	Oral	28 mg/kg	Human
2-butoxyethanol	LD50	Dermal	230 uL/kg	Guinea pig
•	LD50	Oral	320 mg/kg	Rabbit
	LD50	Oral	250 mg/kg	Rat
phosphoric acid	LD50	Dermal	2740 mg/kg	Rabbit
	LD50	Oral	1.25 g/kg	Mouse
	LD50	Oral	1.25 g/kg	Rat
	LD50	Oral	1530 mg/kg	Rat

Target organs : Contains material which causes damage to the following organs: thyroid.

Contains material which may cause damage to the following organs: blood, kidneys, lungs, liver, lymphatic system, cardiovascular system, upper respiratory tract, central

nervous system (CNS).

MIKROKLENE Page: 5/5

Section 12. Ecological information

Ecotoxicity			
Ingredient name	<u>Species</u>	<u>Period</u>	<u>Result</u>
iodine	Daphnia	48 hours	Acute EC50 0.33 mg/L
	Daphnia	96 hours	Acute LC50 0.85 mg/L
	Daphnia	96 hours	Acute LC50 0.59 mg/L
	Fish	96 hours	Acute LC50 0.53 mg/L
	Fish	96 hours	Acute LC50 1.67 mg/L
	Fish	96 hours	Acute LC50 >0.01 mg/L
2-butoxyethanol	Fish	96 hours	Acute LC50 1490 mg/L

Section 13. Disposal considerations

Waste disposal

: The generation of waste should be avoided or minimised wherever possible. Avoid dispersal of spilt material and runoff and contact with soil, waterways, drains and sewers. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Consult your local or regional authorities.

Section 14. Transport information

See shipping documents for specific transportation information.

Section 15. Regulatory information

WHMIS : Not a WHMIS controlled material.

DIN 00435430

This product has been classified in accordance with the hazard criteria of the *Controlled Products Regulations* and the MSDS contains all the information required by the *Controlled Products Regulations*.

Section 16. Other information

Date of issue : 06-August-2008. Responsible name : Regulatory Affairs

1-800-352-5326

Date of previous issue : 18-August-2005.

Notice to reader

The above information is believed to be correct with respect to the formula used to manufacture the product in the country of origin. As data, standards, and regulations change, and conditions of use and handling are beyond our control, NO WARRANTY, EXPRESS OR IMPLIED, IS MADE AS TO THE COMPLETENESS OR CONTINUING ACCURACY OF THIS INFORMATION.